

VIL Epoxy Esters Phenolic & Coumarone Media

TECHNICAL DATA SUMMARY

We summarise below the epoxy esters and oleoresinous media in our standard range. Full information on all products is given on individual technical data sheets.

EPOXY ESTERS

Vil Ref No.	% Non-Volatile Content	Solvent	Viscosity @ 25°C (Poise)	% Fatty Acid	Fatty Acid/Oil Type	Principal Uses
6019	55	White Spirit	15-20	52	Linoleic Rich	Industrial finishes for floor and aluminium paints

PHENOLIC MEDIA

Vil Ref No.	% Non-Volatile Content	Solvent	Viscosity @ 25°C (Poise)	Oil / Resin Ratio	Type	Principal Uses
I593LA	60	Low Aromatic	3.0 - 4.0	2:1	Pure Phenolic	Alkali and water resists primers and sealers

COUMARONE MEDIA

Vil Ref No.	% Non-Volatile Content	Solvent	Viscosity @ 25°C (Poise)	Oil / Resin Ratio	Oil Type	Principal Uses
I064LA	70	Low Aromatic	2.0 - 3.0	3:1	Linseed/Wood	Flexible aluminium paints
I500LA	60	Low Aromatic	3.5 - 5.5	-	Oil Free	Economical aluminium paints

RESINS WITHOUT RIVAL

This information is offered in good faith but without guarantee as to the suitability of the product or the suggested uses, nor can it be assumed that the uses will not infringe any patents.



RESINS

Vil Resins Ltd The Valley Bolton BL2 2DT
Tel: +44(0)1204 388800 Fax: +44(0)1204 362775
Website: www.vilresins.com Email: enquiries@vilresins.co.uk